							PTO/SB/0	5 (4/98)	
Please type a plus sign (+) inside this box -> +			Approved for use through 09/30/2000. OMB 0651-0032 Patent and Trademark Office: U.S. DEPARTMENT OF COMMERCE						
Inder the Paperwork Reduction Act of 1995, no persons are required			Patent and Trademark Unite. 0.s. Department of Collimerator to respond to a collection of information unless it displays a valid QMB control number. Attorney Docket No. 2447-012						
UIILIIY						COLL	N. Louropeo T		
TRANSMITTAL			First Inventor or Application Identifier COHEN. Lawrence T.						
Only for new nonprovision	al applications under 37 C.F.R. § 1.53(b))	Express	Mail Labe	INo. FI	1703992			<u>دي</u>	
APPLICAT	FION ELEMENTS oncerning utility patent application content	s.	ADDI	RESS T	O: Box P	tant Com atent App ington. D	missioner for Patent plication C 20231	2/ n	
* Fee Transn	nittal Form (e.g., PTO/SB/17)		5.	Microfich	ne Comput	ter Progr	am (Appendix)	Ď.	
(Submit an original Specification	ginal and a duplicate for fee processing) [Total Pages] 7	71			d/or Amino		quence Submission	1	
(preferred arra	ingement set forth below)	٦,	(II app		Computer F		e Copy		
	title of the Invention		b.	느				۸	
	 Cross References to Related Applications Statement Regarding Fed sponsored R & D 			_			al to computer copy		
- Reference	c.	<u> </u>	Statement	verifying	identity of above or	pies			
- Background of the Invention			ACCOMPANYING APPLICATION PARTS						
- Brief Summary of the Invention			7. Assignment Papers (cover sheet & document(s))						
 Brief Description of the Drawings (if filed) Detailed Description 			8.		R.§3.73(b) here is an				
- Detailed Description - Claim(s)							nent (if applicable)		
- Abstract of the Disclosure				_	tion Disclo		Copies of	IDS	
3. X Drawing(s) (35 U.S.C. 113) [Total Sheets 2]			10.		ent (IDS)/P				
4. Oath or Declaratio	4. Oath or Declaration [Total Pages]			11. Preliminary Amendment					
a. Newly executed (original or copy)			12. Return Receipt Postcard (MPEP 503) (Should be specifically itemized)						
Copy from a prior application (37 C.F.R. § 1.63(d)			* Small Entity Statement filed in prior application						
(for continuation/divisional with Box 16 completed)				13. Statement(s) Status still proper and desired					
i. DELETION OF INVENTORIS) Signed statement attached deleting inventor(s) named in the prior application,				Certifie	d Copy of I	Priority D	ocument(s)		
	(if foreign priority is claimed)								
TWO TE FOR ITEMS 1 & 13: IN ORDER TO BE ENTITLED TO PAY SMALL ENTITY									
IF ONE FILED IN A PRIO	STATEMENT IS REQUIRED (37 C.F.R. § 1.27), IR APPLICATION IS RELIED UPON (37 C.F.R.	§ 1.28).	1						
16. If a CONTINUIN	G APPLICATION, check appropriate b			uisite infor	mation belo	w and in a	preliminary amendme	ent:	
Continuation					ilication No: Group / Art	Linit	<i>J</i>	_	
Prior application in For CONTINUATION or		sclosure o	f the prior a	Heatie	n from whi	ch an nat	th or declaration is so	upplied	
under Box 4b, is consi	DIVISIONAL APPS only: The entire dis dered a part of the disclosure of the ad oration can only be relied upon when a	companyi portion h	ing continua as been ina	ation or d dvertently	ivisional ap y omitted fr	om the s	ubmitted application	parts.	
Telefolice. The interp	17. CORRES	PONDE	NCE ADD	RESS					
Customer Numbe	er or Bar Code Label (Insert Customer	Vo. or Alla	b bar code	label here	or E	□ Com	espondence address b	elow	
	2	244	,						
Name	PATENT	TRADEMARK O	FFICE						
Address			-						
		- T			700	Code			
City	Teleph	State			210	Fax			
Country	1	W16					29.876	$\overline{}$	
Name (Print/Type)	Tiberiu WEISZ		Reg	gistration I	Vo. (Attorney/			$\overline{}$	
Signature / / / / / / / / / / / / / / / / / / /			t. To	. di	onondina :	Date	August 28, 2000		
	This form is estimated to take 0.2 hour not of time you are required to complete t DO NOT SEND FEES OR COMPLETED Washington, DC 20231.	s to compl his form sh FORMS To	ould be sen O THIS ADD	t to the C	hief Informa END TO: A	ition Office assistant C	er, Patent and Traden commissioner for Pater	nark Office	

Name (Print/Type) Tiberiu WELSZ

Signature

Complete if Known FEE TRANSMITTAL Application Number To Be Assigned for FY 2000 Filing Date Herewith COHEN, Lawrence T First Named Inventor Small Entity payments must be supported by a small entity statement, To Be Assigned otherwise large entity fees must be paid. See Forms PTO/SB/09-12. Examiner Name See 37 C.F.R. §§ 1.27 and 1.28. Group / Art Unit To Be Assigned 245

TOTAL AMOUNT OF PAYMENT (5) 343	Attorney Docket No. 2447-012								
METHOD OF PAYMENT (check one)	FEE CALCULATION (continued)								
The Commissioner is hereby authorized to charge	3. ADDITIONAL FEES								
Indicated fees and credit any overpayments to:	Large Entity Small Entity Fee Fee Fee Fee Fee Fee Code (\$) Code (\$)	Fee Paid							
Account 07-1730	105 130 205 65 Surcharge - late filing fee or oath								
Number	127 50 227 25 Surcharge late provisional filing fee or								
Deposit Account Gottlieb Rackman & Reisman, P.C.	127 50 227 25 Cover sheet.								
Name Gottlieb Hackman & Heisman, 116.	139 130 139 130 Non-English specification								
Charge Any Additional Fee Required	147 2,520 147 2,520 For filing a request for reexamination								
Under 37 CFR §§ 1.16 and 1.17	112 920* 112 920* Requesting publication of SIR prior to Examiner action								
2. Payment Enclosed: Check Money Other Other	113 1,840* 113 1,840* Requesting publication of SIR after Examiner action								
	115 110 215 55 Extension for reply within first month								
FEE CALCULATION	116 380 216 190 Extension for reply within second month								
1. BASIC FILING FEE	117 870 217 435 Extension for reply within third month								
Large Entity Small Entity Fee Fee Fee Fee Description	118 1,360 218 680 Extension for reply within fourth month								
Code (\$) Code (\$) Fee Paid	128 1,850 228 925 Extension for reply within fifth month								
101 690 201 345 Utility filing fee 345	119 300 219 150 Notice of Appeal	\longrightarrow							
106 310 206 155 Design filing fee	120 300 220 150 Filing a brief in support of an appeal								
107 480 207 240 Plant filing fee 108 690 208 345 Reissue filing fee	121 260 221 130 Request for oral hearing								
108 690 208 345 Reissue filing fee 114 150 214 75 Provisional filing fee	138 1,510 138 1,510 Petition to institute a public use proceeding	_							
	140 110 240 55 Petition to revive - unavoidable	\vdash							
SUBTOTAL (1) (\$) 345	141 1,210 241 605 Petition to revive - unintentional								
2. EXTRA CLAIM FEES Fee from	142 1,210 242 605 Utility issue fee (or reissue)								
Extra Claims below Fee Paid	143 430 243 215 Design issue fee								
Total Claims 13 -20** = 0 X	144 500 244 250 1								
Claims Later Tour Claims									
Multiple Dependent	Tourist tourist in processing the processing the processing to the processing the								
**or number previously paid, if greater; For Reissues, see below Large Entity Small Entity	126 240 126 240 Submission of Information Disclosure Stmt	1							
Fee Fee Fee Fee Description Code (\$) Code (\$)	581 40 581 40 Recording each patent assignment per property (times number of properties)								
103 18 203 9 Claims in excess of 20	146 690 246 345 Filing a submission after final rejection (37 CFR § 1.129(a))								
102 78 202 39 Independent claims in excess of 3	149 690 249 345 For each additional invention to be	-							
104 260 204 130 Multiple dependent claim, if not paid	examined (37 CFR § 1.129(b))								
109 78 209 39 ** Reissue independent claims over original patent	Other fee (specify)								
110 18 210 9 ** Reissue claims in excess of 20 and over original patent	Other fee (specify)								
SUBTOTAL (2) (\$) Reduced by Basic Filing Fee Paid SUBTOTAL (3) (\$)									
SUBMITTED BY Complete (d applicable)									
Name (Print/Total) Tiboriu WEISZ									

Information on this form may become public. Credit card information should not be included on this form. Provide credit card information and authorization on PTO-2038.

Date

August 28, 2000

Burden Hour Statement: This form is estimated to take 0.2 hours to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete hits form should be sent to the Chell Information Officer, Patient and Trademark Office, Washington, DC 20231. DO NOT SEND SES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant commissioner for Fatents, Washington, DC 20231.

Inventor(s):

COHEN, Lawrence T.

ELECTRODE ARRAY WITH NON-UNIFORM ELECTRODE SPACING

CERTIFICATE OF EXPRESS MAIL UNDER 37 CFR §1.10

Express Mail Label # EL170399260US Date of Deposit August 28, 2000

I hereby certify that this paper and/or fee is being deposited with the United States Postal Service "Express Mail Post Office to Addresses" service on the date indicated above and is address to: Box Patent Application, Assistant Commissioner for Patents, Washington, DC 2023 1/y

Attorneys for Applicant(s):

Tiberiu WEISZ, Esq. GOTTLIEB RACKMAN & REISMAN, PC 270 Madison Avenue New York, New York 10016-0601 USA

Telephone: 212-684-3900 Telefax: 212-684-3999

ELECTRODE ARRAY WITH NON-UNIFORM ELECTRODE SPACING

Technical Field

5

10

15

20

This invention relates to electrode arrays for intra-cochlear implantation. Background Art

Intracochlear electrode arrays have been successfully utilised for many years as a stimulation mechanism for auditory prostheses. The function of the array is to provide electrical stimuli, by selecting one or more electrodes in the array and delivering a stimulus pulse to the electrodes, so as to produce an auditory percept in a patient.

The array is connected to a receiver-stimulator unit, which in turn typically communicates transcutaneously with an externally worn speech processor and sound transducer.

Over time, many different strategies have been applied both to analyse the speech and sound signals received by the transducer, and to provide appropriate stimuli to selected electrodes in the array so as to optimise the speech and sound perception of the patient.

All commercially available cochlear implants utilise electrode arrays in which the electrodes are substantially equally spaced along the length of the array.

Recently, due to an increased understanding of the physiology of the cochlear, a number of proposals have been made to provide and electrode array which is shaped so as to be located near the inner wall of the scala tympani. By position the array in such a location the electrical stimulation delivered by the electrodes to a particular site on the cochlea is more localised resulting in an improved system providing greater auditory perception to the patient.

It is an object of the present invention to provide an electrode array which improves the fidelity of the reproduction of the audio spectrum in the percept of the cochlear implant recipient, for a given number of electrodes. Summary of the Invention

30

25

10

20

25

30

Broadly, the present invention provides an electrode array in which the electrodes are not evenly spaced, but rather are differentially spaced in order to better target selected regions of the cochlea.

According to one aspect, the present invention provides an intracochlear electrode array in which the electrodes are closer together at the apical end of the array. This may be achieved in various ways – for example, by a uniformly graduated change in spacing, or by selecting two or more regions of the electrode array to have different spacings.

This aspect of the invention is based on several factors. It has been determined that it is desirable for the spacing of electrodes to correspond to uniform intervals along the organ of Corti. While audio stimulation receptors on the outer wall of the scala tympani are generally regularly spaced, receptors on the inner wall tend to be spaced closer together the further one travels inwardly. It has been determined that receptors on the inner wall of the scala timpani are more sensitive than those on the outer wall, and it would therefore be more effective to stimulate these inner receptors rather than the outer ones as is traditionally done. Preferably, the electrode spacing should be determined by the intercepts, along the intended array placement, of lines passing from a modiolar centre point through points spaced at equal increments along the organ of Corti. This arrangement generally maximises the uniformity of spectral coverage for a given number of electrodes, and accordingly the probability of good speech perception by an implant recipient.

According to another aspect, the present invention provides an electrode array with the spacing of electrodes varied so as to provide a higher density of electrodes at specific regions – for example, along a part of the array intended to stimulate one or more regions of the neural structures corresponding to frequency bands which are considered particularly important for speech recognition. This could be based on many different considerations – the essence of this aspect of the invention is simply to provide electrodes at reduced spacing in areas of particular interest.

5

10

15

20

25

30

Brief Description of the Drawings

The invention will now be described with reference to the accompanying figures, in which:

Figure 1 is a schematic illustration of a conventional electrode array in a scala tympani; and

Figure 2 is a schematic illustration of an electrode array with non-uniform spacing of electrodes.

Referring to figure 1, this is based upon an X-Ray of an implanted device having a curved configuration, for example an array according to PCT/AU99/00391 by Cochlear Limited. It will be appreciated that this is a sectional view showing the scala tympani 10, which in fact curves into the page, but for present purposes the invention can be explained with reference to a two dimensioned projection.

Dotted line 15 represents the organ of Corti, on which the audio receptors 12 are disposed at the intersection of radial lines 11 (only one thus labeled) and the organ of Corti 15. Fladial lines 11 are shown extending from the modiolar centre 16, and are of ocurse, purely represented for the purpose of illustrating the present inventive concept. Receptors 12 are composed of neural structures, including spiral ganglion cells, which extend radially inward from the organ of Corti 15. It is in fact these cells which are stimulated by the stimuli produced by electrodes in a cochlear implant.

It will be noted that receptors 12 are disposed at equal intervals along the organ of Corti 15 (at critical bands), even as the curvature increases as the cochlea spirals inwards. The most effective stimulation of these receptors is achieved by direct stimulation by electrodes, and so cochlear implants have been traditionally constructed with electrodes spaced equally to correspond with the spacing of these critical bands. These electrodes are shown as elements 13 on cochlear implant 14.

It has been determined that receptors are more sensitive on the inner wall 18 of the scala timpani 10. Accordingly, it has been found that a better result is achieved by a cochlear implant having electrodes stimulating receptors on the inner wall. To achieve this, the electrodes are caused to lie

10

15

20

25

against the inner wall 18, to make contact with receptors 17 (lying on the intersection of radial lines 11 and the inner wall 18 of scala timpani 10).

As can be seen in figure 2, the receptors 17 on the inner wall 18, are spaced more and more closely together, as they approach the centre of the spiral of the cochiea. Thus, to maintain effective stimulation contact with receptors 17, electrodes 13 of the electrode array 14 are spaced with decreasing separation to each other the closer they approach the apical end of the electrode array 14.

Therefore, with an understanding of the physiology and geometry of the cochlea together with an understanding of the tonotopical nature of the cochlea, an electrode array can be designed to improve the fidelity of the reproduction of the audio spectrum in the percept of the cochlear implant recipient. This can be done by arranging the placement of the electrodes along the electrode array such that the spectral coverage of the electrodes are maximised to ensure optimum stimulation of the cochlea is achieved.

It will be appreciated that in the application of the present invention, the excitation by the electrodes is assumed to be substantially radial.

It may also be desired to take into account two further effects. The structures are considerably more complex than is apparent from the schematics. At the basal end of the scala tympani, the organ of Corti lies closer to the inner wall 18 and the spacing of the most basal electrodes could be reduced to take account of this. At the apical end, there is a greater angular offset between the organ of corti 15 and the underlying cell bodies, and again the spacing could be adjusted to account for this effect.

It will be appreciated by those skilled in the art that the present invention can be readily manufactured by existing techniques, and could be of any desired electrode geometry or cross-sectional shape. The present invention is concerned with the spacing of the electrodes, not their construction

CLAIMS:

- An electrode array for use in a cochlear implant, said electrode array having electrodes selectively positioned along said electrode array in order to better target selected regions of the cochlea.
- An electrode array according to claim 1 wherein the spacing between adjacent electrodes is less at an apical end of the electrode array than at a basal end.
- An electrode array according to claim 1 or 2, wherein one region of the electrode array has electrodes which are spaced from each other differently to electrodes from at least one other region of said electrode array.
- An electrode array according to claim 1 or 2 wherein the spacing between consecutive electrodes is uniformly graduated.
- 5. An electrode array according to claim 3 or 4 wherein said spacing between adjacent electrodes is such as to correspond closely with the spacing of auditory receptors on the inner wall of the scala tympani.
- A method of constructing a cochlear electrode array for implantation into a cochlea of the patient as part of a cochlear implant system, the method including:

determining the regions of the cochlea where stimulation is desired; and

positioning the electrodes along the electrode array in a location or locations that will enable stimulation of the desired site of the cochlea when the electrode array has been inserted.

- 7. A method according to claim 6 wherein the step of positioning the electrodes includes positioning the electrodes such that the spacing between adjacent electrodes is less at the apical end of the electrode array than at the basilar end.
- 8. A method according to claim 6 wherein the step of positioning the electrodes including positioning the electrodes such that the spacing between adjacent electrodes differs in differing regions along the electrode array.
- A method according to claim 6 or 7 wherein the step of positioning the electrodes including positioning the electrodes such that the spacing between consecutive electrodes is uniformly graduated.

ABSTRACT

An electrode array for use with a cochlear implant is disclosed, which has electrodes selectively spaced to better target selected regions of the cochlea. In one form, the spacing between adjacent electrodes decreases towards an apical end of the array allowing the electrodes to better target receptors on the inner wall of the scala timpani of the cochlea.

Fig 1.




Fig 2.

